

1. Dimensions/Waga



Model	Dimensions (mm)												Weight (kg)
	A	A1	B	C	D	E	F	G	K	V	L	P	
EVORA 100	760	745	370	365	420	1040	370	275	540	540	555	280	6,8
EVORA 101	780	765	365	360	425	1045	375	280	540	540	555	280	7,5

A – Seat height

A1 – Seat height according to standard
EN 16139

B – Seat depth

C – Seat surface depth

D – Seat width

E – Overall height

F – Backrest width

G – Backrest length

H – Armrests height

K – Base width

V – Overall width

L – Overall depth

P – Footrest height

2. Materials / Version

2.1. Frame

Hocker 4-leg frame – made of Ø 22 × 1,5 mm steel tube. Protective plastic footrest cap fixed to the crossbar.

Finish options:

– powder-coated in White Aluminium

RAL 9006 (ALU),

– powder-coated in Jet Black RAL 9005 (BL),

– powder-coated in Traffic White RAL 9016 (W),

– powder-coated in Vermilion Red

RAL 030 50 40 (VR),

– powder-coated in Ochre Yellow

RAL 1024 (OY),

– powder-coated in Cashmere NCS S 2005-Y60R (NK),

– powder-coated in Violet Blue RAL 5000 (VB)

- powder-coated in Olive Green RAL 6003 (OG),
- chromium plated (Z).

Chair does not stack.

2.2. Glides

Black plastic glides for soft floors (G20) as standard or hard floors (G20F) as an option.

2.3. Seat and backrest

Wooden shell (0) – made of 6-layer beech plywood, thickness 9.5 mm., natural as a standard, stained or veneer as an option.

Fully upholstered shell (1) – structure made of 6-layer beech plywood, thickness 9.5 mm, covered with flame retardant foam density 55 kg / m³, thickness 15 mm (front) and 9 mm (back part of backrest) as option.

WALL PROTECTION SYSTEM – frame construction enables 60 mm distance between backrest and the wall to prevent it from scratching.

3. Technical regulations, approvals and quality marks for the chairs (for selected product configurations)

Selected configurations have:

Durability certificate:

REMODEX test report – 110 kg –

norm EN 16139.

REMODEX test report – norm BS 5459.